References

- 1. U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics. Report of the National Survey of Lead-Based Paint in Housing Base Report. EPA747-R-95-003. April 1995.
- 2. U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics. A Field Test of Lead-Based Paint Testing Technologies: Technical Report, EPA 747-R-95-002b. May 1995.
- 3. U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics. Toxicity Characteristic Leaching Procedure, Method 1311. Test Methods of Environmental Testing Solid Wastes Physical and Chemical Methods, SW-846 (3rd ed.). November 1986.
- U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics. Stabilization/Solidification of CERLA and RCRA Wastes. EPA/625/6-89/022. May 1989.
- 5. Hock, V., C. Gustafson, D. Cropek, and S. Drozdz. U.S. Army Corps of Engineers, Construction Engineering Research Laboratories. Demonstration of Lead-Based Paint Removal and Chemical Stabilizer Using Blastox. Technical Report FEAP-TR-96/20. October 1996.
- 6. U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics. Stabilization of Lead-Based Paint Waste. October 1998 (Draft).
- 7. U.S. Patent Number 5,674,108. Method for Removing Coatings Which Create Hazardous Products. October 7, 1997.
- 8. Steel Structures Painting Council. Guide for Containing Debris Generated During Paint Removal Operations. SSPC Guide 6. December 11, 1995.
- 9. American Society of Testing Materials. Standard Test Method for Measurement of Dry Film Thickness of Protective Coating Systems by Destructive Means. ASTM Standard Method D 4138 88. April 1988.

- 10. U.S. Department of Housing and Urban Development. *Chapter 7: Lead-Based Paint Inspection* (1997 Revision). In: *Guidelines for the Evaluation and Control of Lead-Based Paint Hazards in Housing*, HUD, Washington, D.C. June 1995.
- 11. U.S. Environmental Protection Agency. Performance Characteristic Sheet, Edition No. 4. Niton Corporation, Models: XL-309, 701-A, 702-A, and 703-A Spectrum Analyzers. April 17, 1998.
- 12. Rubow, K. L., V. A. Marple, and J. Olin. A personal cascade impactor: design, evaluation, and calibration. *Am. Ind. Hyg. Assoc. J.* 48 (6): 532-538 (1987).
- 13. U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics. Chapter Nine *Sampling Plan*. Test Methods of Environmental Testing Solid Wastes Physical and Chemical Methods, SW-846 (3rd ed.). November 1986.
- 14. American Industrial Hygiene Association. Environmental Lead Laboratory Accreditation Program.
- U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics.
 Contract Laboratory Program Statement of Work for Inorganic Analysis,
 Document ILMO40. 1985.
- U.S. Environmental Protection Agency. Field Demonstration of Clean Technologies for Removal of Lead-Based Paint from Residential Housing Units in Buffalo, New York. Final Report. September 1996.
- 17. American Society of Testing Materials. Standard Practice for Reducing Samples of Aggregate to Testing Size. ASTM Standard Method C 702 93. September 15, 1993.
- 18. Bishop, P. L. 1988. Leaching of inorganic hazardous constituents from stabilized/solidified hazardous wastes. Hazardous Waste & Hazardous Materials 5(2): 129-143.
- 19. Buskowski, J. M., J. H. Boy, X. Zhu, T. D. Race, and K. A. Reinhold. Immobilization chemistry in Portland cement stabilized paint blast media wastes. Environmental and Waste Management Issues in the Ceramic Industry II 45: 155-163. 1994.
- 20. Technical Bulletin: Determining Proper Blastox® Blend Ratios. TB-007 (Issued 10-98), The TDJ Group Inc., Cary, Illinois 60013.